



PVC-Gasket,
transparent

Hexagon nut G1/2 SW36
with 2x M4 female thread for anti-rotation

Media	MM
Compressed air	38
Nitrogen	35
Carbon dioxide	40
Argon	47
Helium	48

Max. bench thickness: 50 mm
Bench drilling: $\phi 21+1$ mm



UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS IN MM

THIS DRAWING IS PROPERTY OF ILA GMBH, IT CAN NOT BE PUBLISHED OR COMMUNICATED WITHOUT CONSENT OF ILA GMBH

WEIGHT: 1002.213g

DESCRIPTION

	DATE	NAME
CREATED	15.05.2023	C. Vowinkel
CHECKED	15.05.2023	C. Vowinkel
RELEASED	15.05.2023	C. Vowinkel

Bench mounted single turret valve for 2.0 technical gases. Inlet connection: 70mm shank with G1/2 male thread. Height: 90mm. Stand out of 155mm. Fixed serrated brass hose nozzle. Molded nylon handle with media indication according to EN 13792. Needle cone headwork, 5/4 x 360°. RAL 7035 powder coated finish.



DRAWING NUMBER:
34.3000.26MM.2080

A3

INDEX	CHANGE	DATE	NAME

SCALE: 1 : 1,5

PAGE: 1 / 1