



Media **MM**

		Potable water	03
		Non-potable water	06

Max. bench thickness: 50 mm
 Bench drilling: $\varnothing 21+1$ mm

PVC-Gasket, transparent

Hexagon nut G1/2 SW36 with 2x M4 female thread for anti-rotation

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS IN MM

WEIGHT: 1621.73g

DATE: 16.03.2023 NAME: D.Kheradvar

CHECKED
 RELEASED

THIS DRAWING IS PROPERTY OF ILA GMBH, IT CAN NOT BE PUBLISHED OR COMMUNICATED WITHOUT CONSENT OF ILA GMBH

DESCRIPTION
 Bench mounted T-shaped two way valve on a column for water. Inlet connection: 70mm shank with G1/2 male thread. Height: 300mm. 150mm stand out of each valve. Total stand out of 300mm. Removable plastic hose nozzle. Molded nylon handle with media indication according to EN 13792. Rubber compression control headwork: 2 x 360°. RAL 7035 powder coated finish. Bench mounted T-shaped two way valve on a column for water. Inlet connection: 70mm shank with G1/2 male thread. Height: 300mm. 150mm stand out of each valve. Total stand out of 300mm. Removable plastic hose nozzle. Molded nylon handle with media indication according to EN 13792. Rubber compression control headwork: 2 x 360°. RAL 7035 powder coated finish.

DRWAING NUMBER.
 14.1500.20MM.0390 A3

SCALE: 1 : 2 PAGE: 1 / 1



INDEX	CHANGE	DATE	NAME